

Technical Data Sheet Kraft Paper Airbags (All PLY'S)

Details	1 PLY Kraft	2 PLY Kraft	4 PLY Kraft
Working Pressure (Bar)	0.10	0.20	0.30
Working Pressure (PSI)	1.5	2.9	4.4
Recommended Use	Truck & Container	Truck & Container	Container, Ship & Train
PE Gram/m2	60mic	80mic	100mic
Dimensions	From 60cm's to 240cm's in Length all sizes!		
Type of Valve	Fast Flow Turbo Venturi Valve		
Outer Layer	Kraft Paper		
Inner Layer	On the inside coex multi layers of LDPE quality film (recyclable #4)		
Valve	LDPE (recyclable material #4)		
Colour of dunnage bag	Brown		
Colour of valve	Black and Yellow		
Colour of Label	Black		
Pallet dimensions	100x120x125cm's		
Raw Material	All our products are products with virgin materials (PP and PE)		





Air Bag Production
ABP

Safe Shipping Starts With Safe Loading!



Kraft paper dunnage air bags have an outstanding load stabilizing capacity, withstanding tons of pressure and resistance to load shifting. The bags are constructed of multiple layers of high strength extensible Kraft paper and inner liner is constructed of coextruded polyethylene film for added protection against loss of air pressure.



1105 Budapest , Gyömrői út 115 Hungary



info@abpairbag.eu



+36 (70) 657 61-99



www.abpairbag.eu